

MICRO fraises


Micro fraises

Mikro Fräser

Micro end mills

Micro frese

2	1	0	1	2	0	3	0	M	210.120.30	210.120.30M
MD HM/SC MG KX10	MICRO fraises MIKRO Fräser MICRO end mills MICRO frese			Z2 		$\lambda 30^\circ$ $\gamma \sim 10^\circ$		PSNM		



OPTI
micro



$l1 = 0.75 \times D$

Type N

Norme OPTI

D _{+/-0.01}	d _{h5}	l ₁	L	Z	Non revêtu	Revêtu PSNM
0.3	3	0.25	39	2	210.120.30-00.3	210.120.30M-00.3
0.4	3	0.3	39	2	210.120.30-00.4	210.120.30M-00.4
0.5	3	0.37	39	2	210.120.30-00.5	210.120.30M-00.5
0.6	3	0.45	39	2	210.120.30-00.6	210.120.30M-00.6
0.7	3	0.53	39	2	210.120.30-00.7	210.120.30M-00.7
0.8	3	0.6	39	2	210.120.30-00.8	210.120.30M-00.8
0.9	3	0.67	39	2	210.120.30-00.9	210.120.30M-00.9
1	3	0.75	39	2	210.120.30-01	210.120.30M-01

INEO
Tech
>>> p 138