

MICRO fraises


Micro fraises

Mikro Fräser

Micro end mills

Micro frese

2	1	0	1	2	1	3	0	M	210.121.30	210.121.30M
MD HM/SC MG KX10	MICRO fraises MIKRO Fräser MICRO end mills MICRO frese					$\lambda 30^\circ$ $\gamma \sim 10^\circ$		PSNM		



OPTI
micro



$l1 = 1.5 \times D$

Type N

Norme OPTI

D _{+/-0.01}	d _{h5}	l ₁	L	Z	Non revêtu	Revêtu PSNM
0.1	3	0.15	39	2	210.121.30-00.1	
0.15	3	0.2	39	2	210.121.30-00.15	
0.2	3	0.3	39	2	210.121.30-00.2	210.121.30M-00.2
0.25	3	0.35	39	2	210.121.30-00.25	210.121.30M-00.25
0.3	3	0.45	39	2	210.121.30-00.3	210.121.30M-00.3
0.4	3	0.6	39	2	210.121.30-00.4	210.121.30M-00.4
0.5	3	0.75	39	2	210.121.30-00.5	210.121.30M-00.5
0.6	3	0.9	39	2	210.121.30-00.6	210.121.30M-00.6
0.7	3	1.05	39	2	210.121.30-00.7	210.121.30M-00.7
0.8	3	1.2	39	2	210.121.30-00.8	210.121.30M-00.8
0.9	3	1.35	39	2	210.121.30-00.9	210.121.30M-00.9
1	3	1.5	39	2	210.121.30-01	210.121.30M-01
1.1	3	1.65	39	2	210.121.30-01.1	210.121.30M-01.1
1.2	3	1.8	39	2	210.121.30-01.2	210.121.30M-01.2
1.3	3	1.95	39	2	210.121.30-01.3	210.121.30M-01.3
1.4	3	2.1	39	2	210.121.30-01.4	210.121.30M-01.4
1.5	3	2.25	39	2	210.121.30-01.5	210.121.30M-01.5
1.6	3	2.4	39	2	210.121.30-01.6	210.121.30M-01.6
1.7	3	2.55	39	2	210.121.30-01.7	210.121.30M-01.7
1.8	3	2.7	39	2	210.121.30-01.8	210.121.30M-01.8
1.9	3	2.85	39	2	210.121.30-01.9	210.121.30M-01.9
2	3	3	39	2	210.121.30-02	210.121.30M-02

INEO
Tech
>>> p 138